

STOCK AVAILABLE EX MELBOURNE WAREHOUSE AS AT 1ST OCTOBER 2008
 FOR CURRENT PRICING CONTACT AIRPORT METALS SALES DEPARTMENT ON ABOVE NUMBERS

ALUMINIUM ROD



Specification	Diameter Inches
2024-T351	0.500
2024-T351	0.625
2024-T351	0.750
2024-T351	0.875
2024-T351	1.000
2024-T351	1.125
2024-T351	1.250
2024-T351	1.375
2024-T351	1.500
2024-T351	2.000
2024-T351	2.500
2024-T351	3.000
2024-T351	4.000
2024-T351	5.000
2024-T3511	2.250
2024-T4	0.250
2024-T4	0.375
6061-T6	0.250
6061-T651	0.500
6061-T651	0.625
6061-T651	0.750
6061-T651	1.000
6061-T651	1.500
6061-T651	1.625
6061-T651	2.000
6061-T651	2.250
6061-T651	2.500
6061-T651	3.000
6061-T651	3.500
7075-T651	0.500
7075-T651	0.750
7075-T651	1.000
7075-T651	1.500
7075-T651	2.000
7075-T651	2.500
7075-T651	3.000
7075-T651	4.000

ALUMINIUM BRONZE ROD

Specification	Diameter Inches
AMS 4640	0.500
AMS 4640	0.625
AMS 4640	0.750
AMS 4640	1.000
AMS 4640	1.375
AMS 4640	1.750
AMS 4640	2.000
AMS 4640	2.500
AMS 4640	2.750

CHROME MOLY ROD



Specification MIL-S-6758

Condition	Diameter Inches
4130 D4	0.250
4130 F4	0.500
4130 F4	0.625
4130 D4	0.750
4130 F4	0.750
4130 D4	1.000
4130 F4	1.000
4130 D4	1.250
4130 F4	1.250
4130 F4	1.500
4130 D4	2.000
4130 D4	2.250
4130 D4	2.500
4130 D4	2.750

TITANIUM ROD

Specification	Diameter Inches
AMS 4928 6AL/4V	1.000
AMS 4928 6AL/4V	1.500
AMS 4928 6AL/4V	2.000

STAINLESS STEEL ROD



Type	Condition	Specification	Diameter Inches
Nitronic 60	Sol Heat Treated	AMS 5848	0.100
15-5PH	Annealed	AMS 5659	1.000
15-5PH	Annealed	AMS 5659	2.000
17-4PH	Annealed	AMS 5643	1.125
17-4PH	Annealed	AMS 5643	1.750
304	Annealed	AMS 5647	0.875
321	Annealed	AMS 5645	0.375
321	Annealed	AMS 5645	0.625
321	Annealed	AMS 5645	0.750
321	Annealed	AMS 5645	0.875
321	Annealed	AMS 5645	1.000
321	Annealed	AMS 5645	1.500
321	Annealed	AMS 5645	2.000
347	Annealed	AMS 5646	0.250
347	Annealed	AMS 5646	1.750
316	Annealed	AMS 5648	0.375
431	Heat Treated	BSS80D	0.3125
431	Heat Treated	BSS80D	0.375
431	Heat Treated	BSS80D	0.625
431	Heat Treated	BSS80D	1.500
431	Heat Treated	BSS80D	1.750
431	Heat Treated	BSS80D	2.000
431	Heat Treated	BSS80D	2.500
431	Heat Treated	BSS80D	2.750

ALLOY STEEL ROD



Specification	Diameter Inches
AMS 5759J	0.125
BSS154	0.3125
BSS99G Br, Hard & Temp	0.3125
BSS154D Br, Heat Treated	0.500
BSS99G Br, Softened	0.500
BSS99G Br, Hard & Temp	0.750
BSS99G Br, Hard & Temp	1.000
BSS99G Br, Softened	1.500
BSS154	6.000

HASTELLOY ROD

Specification	Diameter Inches
AMS 5754 Sol Heat Treated	0.500
AMS 5754 Sol Heat Treated	1.000